

## 2281 Multipoint Switch, 1 or 2 SPDT Relay, 2-4 Electrodes



- Conductive Principle
- Relay Output: 1 or 2 SPDT
- Power Supply: 24V...240V AC or DC 24V AC/DC
- Max. voltage rating 250V AC1, 24V DC
- Probes: 2,3,4 + 1 Reference
- Electrode Material: Stainless Steel 1.4571
- Electrode Length: 0.5, 1.0, 1.5 m (max. 3 m)
- Electrode Separator, Material PP ( KLP-201)

MFR #	Length	Process Connection	Sensor Type	Code
2281-S-BT-2		1 1/2" BSP		<b>159 300 250</b>
2281-S-BT-3		1 1/2" BSP		<b>159 300 251</b>
2281-S-BT-4		1 1/2" BSP		<b>159 300 252</b>
KLN-205	0.5 m		Stainless Steel	<b>159 300 253</b>
KLN-210	1.0 m		Stainless Steel	<b>159 300 254</b>
KLN-215	1.5 m		Stainless Steel	<b>159 300 255</b>
KLP-201				<b>159 300 257</b>
2281-1-Relay				<b>159 300 258</b>
2281-2-Relay				<b>159 300 259</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>