



Main features of the AIR SIL range



Forced ventilation which allows better cooling of the machine's internal parts (on AIR SIL 2-3 models).



Intake silencer supplementary to significantly reduce the noise level (on AIR SIL 2-3 models).



Easy maintenance, these machines were designed with particular attention to the simplicity of maintenance operations on all internal components.

Low noise levels

Quiet compressors with the lowest noise level available in the category.



120 dB(A)



100 dB(A)



Standard Piston Compressors

74-77 dB(A)



NuAir Silenced
63-65 dB(A)



62 dB(A)

AIR SIL1 B2800B & AIR SIL1 B3800B



OIL



2 & 3 HP



100 ltr



MAX
10 bar



65 dB(A)



Equipped with front door opening to facilitate access and maintenance of all internal components. The oil level is easily visible and top-up is simple thanks to the convenient positioning of the pump unit.



A control panel with a double manometer, pressure gauge, counter and power switch with an ON/OFF switch located on the device to facilitate its reading and use.



The cabinet is lined with sound-absorbing panels that guarantee an excellent level of soundproofing.



Belt tensioner skid that adjusts the tension of the belt and facilitates its replacement.



AIR SIL1 B3800B/3CM/100

AIR SIL1 B2800B/2CM/100

FPS Code	Description	Type	Control	Rec. Ltr	Volt v	Motor kW	HP	Capacity L/Min	CFM	Pressure Bar	Psi	Dimensions L x W x H (mm)	Weight Kgs
S-28FR404FPS078	AIRSIL1 B2800B/2CM/100 UK	Portable	DOL	100	230	1.5	2	255	9	10	145	1140 x 610 x 1200	113
S-28FR504FPS079	AIRSIL1 B2800B/3CM/100 UK	Portable	DOL	100	230	2.2	3	330	11.6	10	145	1140 x 610 x 1300	116
S-28FR541FPS080	AIRSIL1 B2800B/3CT/100	Portable	DOL	100	400	2.2	3	330	11.6	10	145	1140 x 610 x 1300	116
S-36FR504FPS076	AIRSIL1 B3800B/3CM/100	Portable	DOL	100	230	2.2	3	330	11.6	10	145	1200 x 470 x 1000	109
S-36FR541FPS077	AIRSIL1 B3800B/3CT/100	Portable	DOL	100	400	2.2	3	330	11.6	10	145	1200 x 470 x 1000	109

AIR SIL2 NB5/5.5FT & NB7/7.5FT



OIL
 5.5 & 7.5 HP
 11 bar
 64 dB(A)

Powerful pump which ensures extremely high performance and reliability at maximum levels.



Equipped with a front panel which opens up to provide easy access and maintenance of all internal components. The oil level is clearly visible and topping up is simple thanks to the convenient position of the pump.



The control panel, which includes all necessary instrumentation for machine operation, is positioned in such a way so as to facilitate reading. The versions with star-delta have an electronic switchboard with warning lights which signal any faults.



AIR SIL2 NB5/5.5FT/270 & NB7/7.5FT/270

OIL
 5.5 & 7.5 HP
 270 ltr
 11 bar
 64 dB(A)



Equipped with supplementary silencers on the compressor intake in order to increase noise reduction.



Belt tensioner skid that adjusts the tension of the belt and facilitates its replacement.



Easily transported on a pallet truck even by only one person with a pallet jack thanks to the bar located between the feet at the base of the tank.



FPS Code	Description	Type	Control	Rec. Ltr	Volt v	Motor kW	HP	Capacity L/Min	CFM	Pressure Bar	Psi	Dimensions L x W x H (mm)	Weight Kgs
S-N5AT701FPS081	AIR SIL2 NB5/5.5FT	Stationary	DOL	-	400	4	5.5	640	22.6	11	160	1080 x 780 x 1050	167
S-N5NT701FPS083	AIR SIL2 NB5/5.5FT/270	Stationary	DOL	270	400	4	5.5	640	22.6	11	160	1544 x 695 x 1505	242
S-N7AT801FPS082	AIR SIL2 NB7/7.5FT	Stationary	DOL	-	400	5.5	7.5	840	29.7	11	160	1180 x 780 x 1050	174
S-N7NT801FPS084	AIR SIL2 NB7/7.5FT/270	Stationary	DOL	270	400	5.5	7.5	840	29.7	11	160	1544 x 695 x 1505	249

AIR SIL3 NB10/10FT SD



OIL
 10 HP
 11 bar
 64 dB(A)

Powerful pump which ensure extremely high performance and reliability at maximum levels.



Equipped with a front panel which opens up to provide easy access and maintenance of all internal components. The oil level is clearly visible and topping up is simple thanks to the convenient position of the pump.



The control panel, which includes all necessary instrumentation for machine operation, is positioned in such a way so as to facilitate reading. The versions with star-delta have an electronic switchboard with warning lights which signal any faults.



Star-delta starter switchboard on 7.5kW / 10HP model.



Equipped with supplementary silencers on the compressor intake in order to increase noise reduction.



AIR SIL3 NB10/10FT/500 SD

OIL
 10 HP
 500 ltr
 11 bar
 64 dB(A)



Belt tensioner skid that adjusts the tension of the belt and facilitates its replacement.



Easily transported on a pallet truck even by only one person with a pallet jack thanks to the bar located between the feet at the base of the tank.



Forced ventilation for better cooling. For the star-delta starter versions the cooling fan is thermostatic.



FPS Code	Description	Type	Control	Rec. Ltr	Volt v	Motor kW	HP	* Capacity L/Min	CFM	Pressure Bar	Psi	Dimensions L x W x H (mm)	Weight Kgs
S-N1AT905FPS085	AIR SIL3 NB10/10FT SD	Stationary	DOL	-	400	7.5	10	1230	43.4	11	160	1290 x 940 x 1040	252
S-N1TT905FPS086	AIR SIL3 NB10/10FT/500 SD	Stationary	DOL	500	400	7.5	10	1230	43.4	11	160	2005 x 895 x 1660	375

E & OE / Images shown are for illustration purposes only & may vary from the actual product

* capacity refers to piston displacement



FPS Air Compressors Ltd
 Fax: +44(0) 1844 390955
 sales@fps-compressors.co.uk
 Unit 5, Tower Estate, Warpsgrove Lane,
 Chalgrove, Oxon, OX44 7XZ



SALES

SUPPORT

01865 892620

01865 892621

www.fps-compressors.co.uk