




Robust brass coupling with numerous connection options. Preferred application is the compressed air technology. Also particularly suited to use with water due to the brass valve. Coupling system with single-hand operation. Plug design optimised through greater insert depth.

- Available on request:
  - in brass material with nickel plating
  - with additional end connections
  - other seals for different temperature ranges and fluids



ARO Profile



KA
Single Shut-Off

**Working Pressure\*:**  
up to 35 bar

**Material:**


- Coupling: Brass
- Plug: Brass
- Seals: NBR

**Working Temperature:**  
-20°C up to +100°C (NBR)


**Flow Rate Air:**  
660 l/min.  
inlet pressure 6 bar, pressure drop 0.5 bar

**Flow Rate Water:**  
9.1 l/min.  
pressure drop 0.5 bar

\* maximum static working pressure with design factor 4 to 1.




Single Shut-Off



Single Shut-Off

## 14KAAW Coupler with valve, Male Thread



Brass, NBR



A	HEX	L	L1	D
G1/4 <a href="#">14KAAW13MPX</a>	22	43	9	25
G3/8 <a href="#">14KAAW17MPX</a>	22	43	9	25
G1/2 <a href="#">14KAAW21MPX</a>	22	46	12	25

## 14KATF Coupler with valve, Hose Barb


Brass, NBR



A	HEX	L	L1	D
6 <a href="#">14KATF06MPX</a>	21	60	25	25
8 <a href="#">14KATF08MPX</a>	21	60	25	25
9 <a href="#">14KATF09MPX</a>	21	60	25	25
10 <a href="#">14KATF10MPX</a>	21	60	25	25
13 <a href="#">14KATF13MPX</a>	21	60	25	25

## 14KAIW Coupler with valve, Female Thread

Brass, NBR






A	HEX	L	L1	D
G1/4 <a href="#">14KAIW13MPX</a>	22	43	9	25
G3/8 <a href="#">14KAIW17MPX</a>	22	43	9	25
G1/2 <a href="#">14KAIW21MPX</a>	24	46	12	25

 Single Shut-Off

## 22SFA Plug without valve, Male Thread


Nickel-plated steel or brass





A			HEX	L	L1	Version
R1/8	<a href="#">22SFAK10SXN</a>		12	35	9	Nickel-plated steel
R1/4	<a href="#">22SFAK13SXN</a>	<a href="#">9084 22 13</a>	14	41	12	Nickel-plated steel
R1/4	<a href="#">22SFAK13MXX</a>		14	41	12	Brass
G1/4	<a href="#">22SAFW13MXX</a>		14	41	12	Brass
R3/8	<a href="#">22SFAK17SXN</a>	<a href="#">9084 22 17</a>	17	41	12	Nickel-plated steel
G3/8	<a href="#">22SAFW17MXX</a>		17	41	12	Brass
R1/2	<a href="#">22SFAK21SXN</a>	<a href="#">9084 22 21</a>	22	46	17	Nickel-plated steel
G1/2	<a href="#">22SAFW21MXX</a>		22	46	17	Brass

## 22SFIW Plug without valve, Female Thread


Nickel-plated steel or brass





A			HEX	L	L1	Version
G1/4	<a href="#">22SFIW13SXN</a>	<a href="#">9086 22 13</a>	17	35	9	Nickel-plated steel
G1/4	<a href="#">22SFIW13MXX</a>		17	35	9	Brass
G3/8	<a href="#">22SFIW17SXN</a>	<a href="#">9086 22 17</a>	19	35	10	Nickel-plated steel
G1/2	<a href="#">22SFIW21SXN</a>	<a href="#">9086 22 21</a>	24	35	12	Nickel-plated steel

## 22SFTF Plug without valve, Hose Barb

Nickel-plated steel or brass



A			L	L1	D	Version
6	<a href="#">22SFTF06SXN</a>	<a href="#">9085 22 06</a>	49	25	12	Nickel-plated steel
6	<a href="#">22SFTF06MXX</a>		49	25	12	Brass
8	<a href="#">22SFTF08SXN</a>	<a href="#">9085 22 08</a>	49	25	12	Nickel-plated steel
9	<a href="#">22SFTF09SXN</a>	<a href="#">9085 22 09</a>	49	25	12	Nickel-plated steel
10	<a href="#">22SFTF10SXN</a>	<a href="#">9085 22 10</a>	49	25	12	Nickel-plated steel
10	<a href="#">22SFTF10MXX</a>		49	25	12	Brass
13	<a href="#">22SFTF13SXN</a>	<a href="#">9085 22 13</a>	49	25	15	Nickel-plated steel