



Tube to Male Pipe

NPT Male Metric Elbow For metric tube





| CPI™ PART NO. | A-LOK® PART NO. | INTER- CHANGES WITH | MILLIMETERS | | | | | | INCHES |
|------------------|--------------------|---------------------------|--------------|---------------|------|------|------|------|----------|
| | | | TUBE O.D. | NPT THREAD | C | H | L | R | W HEX |
| CBZ 3-1/8 | M3MSEL1/8N | 3MO-2-2 | 3 | 1/8 | 23,6 | 17,8 | 17,0 | 9,7 | 7/16 |
| CBZ 3-1/4 | M3MSEL1/4N | 3MO-2-4 | 3 | 1/4 | 24,6 | 23,4 | 18,0 | 14,2 | 1/2 |
| CBZ 4-1/8 | M4MSEL1/8N | 4MO-2-2 | 4 | 1/8 | 25,4 | 18,8 | 19,2 | 9,7 | 1/2 |
| CBZ 4-1/4 | M4MSEL1/4N | 4MO-2-4 | 4 | 1/4 | 26,2 | 25,4 | 19,6 | 14,2 | 1/2 |
| CBZ 6-1/8 | M6MSEL1/8N | 6MO-2-2 | 6 | 1/8 | 27,0 | 18,8 | 19,6 | 9,7 | 1/2 |
| CBZ 6-1/4 | M6MSEL1/4N | 6MO-2-4 | 6 | 1/4 | 27,0 | 23,4 | 19,6 | 14,2 | 1/2 |
| CBZ 6-3/8 | M6MSEL3/8N | 6MO-2-6 | 6 | 3/8 | 29,8 | 26,2 | 22,4 | 14,2 | 11/16 |
| CBZ 6-1/2 | M6MSEL1/2N | 6MO-2-8 | 6 | 1/2 | 31,8 | 33,0 | 24,4 | 19,0 | 13/16 |
| CBZ 8-1/8 | M8MSEL1/8N | 8MO-2-2 | 8 | 1/8 | 28,8 | 19,8 | 21,3 | 9,7 | 9/16 |
| CBZ 8-1/4 | M8MSEL1/4N | 8MO-2-4 | 8 | 1/4 | 28,8 | 24,4 | 21,3 | 14,2 | 9/16 |
| CBZ 8-3/8 | M8MSEL3/8N | 8MO-2-6 | 8 | 3/8 | 30,6 | 26,2 | 23,1 | 14,2 | 11/16 |
| CBZ 8-1/2 | M8MSEL1/2N | 8MO-2-8 | 8 | 1/2 | 32,7 | 33,0 | 25,2 | 19,1 | 13/16 |
| CBZ 10-1/8 | M10MSEL1/8N | 10MO-2-8 | 10 | 1/8 | 31,5 | 21,6 | 23,9 | 9,7 | 11/16 |
| CBZ 10-1/4 | M10MSEL1/4N | 10MO-2-4 | 10 | 1/4 | 31,5 | 26,2 | 23,9 | 14,2 | 11/16 |
| CBZ 10-3/8 | M10MSEL3/8N | 10MO-2-6 | 10 | 3/8 | 31,5 | 26,2 | 23,9 | 14,2 | 11/16 |
| CBZ 10-1/2 | M10MSEL1/2N | 10MO-2-8 | 10 | 1/2 | 33,5 | 33,0 | 25,9 | 19,0 | 13/16 |
| CBZ 12-1/4 | M12MSEL1/4N | 12MO-2-4 | 12 | 1/4 | 36,0 | 28,2 | 25,9 | 14,2 | 13/16 |
| CBZ 12-3/8 | M12MSEL3/8N | 12MO-2-6 | 12 | 3/8 | 36,0 | 28,2 | 25,9 | 14,2 | 13/16 |
| CBZ 12-1/2 | M12MSEL1/2N | 12MO-2-8 | 12 | 1/2 | 36,0 | 33,0 | 25,9 | 19,0 | 13/16 |
| CBZ 12-3/4 | M12MSEL3/4N | 12MO-2-12 | 12 | 3/4 | 39,8 | 36,8 | 29,7 | 19,0 | 1-1/16 |
| CBZ 15-1/2 | M15MSEL1/2N | 15MO-2-8 | 15 | 1/2 | 38,0 | 35,1 | 27,9 | 19,0 | 15/16 |
| CBZ 16-3/8 | M16MSEL3/8N | 16MO-2-6 | 16 | 3/8 | 38,0 | 30,2 | 27,9 | 14,2 | 15/16 |
| CBZ 16-1/2 | M16MSEL1/2N | 16MO-2-8 | 16 | 1/2 | 38,0 | 35,1 | 27,9 | 19,0 | 15/16 |
| CBZ 16-3/4 | M16MSEL3/4N | 16MO-2-12 | 16 | 3/4 | 39,8 | 36,8 | 29,7 | 19,0 | 1-1/16 |
| CBZ 18-1/2 | M18MSEL1/2N | 18MO-2-8 | 18 | 1/2 | 39,8 | 36,8 | 29,7 | 19,0 | 1-1/16 |
| CBZ 18-3/4 | M18MSEL3/4N | 18MO-2-12 | 18 | 3/4 | 39,8 | 36,8 | 29,7 | 19,0 | 1-1/16 |
| CBZ 20-1/2 | M20MSEL1/2N | 20MO-2-8 | 20 | 1/2 | 44,6 | 41,7 | 34,5 | 19,0 | 1-3/8 |
| CBZ 20-3/4 | M20MSEL3/4N | 20MO-2-12 | 20 | 3/4 | 44,6 | 41,7 | 34,5 | 19,0 | 1-3/8 |
| CBZ 22-3/4 | M22MSEL3/4N | 22MO-2-12 | 22 | 3/4 | 44,6 | 41,7 | 34,5 | 19,0 | 1-3/8 |
| CBZ 25-3/4 | M25MSEL3/4N | 25MO-2-12 | 25 | 3/4 | 49,1 | 41,7 | 36,8 | 19,0 | 1-3/8 |
| CBZ 25-1 | M25MSEL1N | 25MO-2-16 | 25 | 1 | 49,1 | 46,5 | 36,8 | 23,9 | 1-3/8 |

NOTE: C dimension is typical finger-tight.

Dimensions for reference only, subject to change.

BSP Taper Male Elbow For fractional tube



| CPI™ PART NO. | A-LOK® PART NO. | INTER- CHANGES WITH | INCHES | | | | | | |
|------------------|--------------------|---------------------------|--------------|----------------|------|------|------|-----|----------|
| | | | TUBE O.D. | BSPT THREAD | C | H | L | R | W HEX |
| 4-2K CBZ | 4MSEL2K | 400-2-2RT | 1/4 | 1/8 | 1.06 | 0.75 | 0.77 | .38 | 1/2 |
| 4-4K CBZ | 4MSEL4K | 400-2-4RT | 1/4 | 1/4 | 1.06 | 0.94 | 0.77 | .56 | 9/16 |
| 4-6K CBZ | 4MSEL6K | 400-2-6RT | 1/4 | 3/8 | 1.17 | 1.05 | 0.88 | .56 | 11/16 |
| 4-8K CBZ | 4MSEL8K | 400-2-8RT | 1/4 | 1/2 | 1.25 | 1.32 | 0.96 | .75 | 13/16 |
| 5-4K CBZ | 5MSEL4K | 500-2-4RT | 5/16 | 1/4 | 1.13 | 0.98 | 0.84 | .38 | 9/16 |
| 6-4K CBZ | 6MSEL4K | 600-2-4RT | 3/8 | 1/4 | 1.20 | 1.02 | 0.91 | .56 | 5/8 |
| 6-6K CBZ | 6MSEL6K | 600-2-4RT | 3/8 | 3/8 | 1.23 | 1.05 | 0.97 | .56 | 11/16 |
| 8-6K CBZ | 8MSEL6K | 810-2-6RT | 1/2 | 3/8 | 1.42 | 1.13 | 1.02 | .56 | 13/16 |
| 8-8K CBZ | 8MSEL8K | 810-2-8RT | 1/2 | 1/2 | 1.42 | 1.32 | 1.02 | .75 | 13/16 |

NOTE: C dimension is typical finger-tight.

Dimensions for reference only, subject to change.



Hanley Controls Clonmel Ltd.

Gortnafleur, Clonmel, Co. Tipperary

tel: + 353 52 6122722

email: info@hccl.ie

web: www.hccl.ie

Single/Double Ferrule Instrument
Compression Fittings